

# LAUFEN INSTALLATION SYSTEM

## CW1

### Concealed frame with cistern for wallhung WC 89466.0



#### TECHNICAL DATA

Order no.	89466.0	Weight	14,5 kg
Certified to	EN 14055	Mounting acc. incl.	Fastening set to floor and wall, WC connection set, tiling set, protection caps (for WC connection pipes) and protection tubes for M12 threaded rods, angle valve 1/2".
matching for	All LAUFEN wallhung toilets	Mounting acc. excl.	Sound insulation set, order no. 89269.6
Specifications	For mounting in front of a solid or drywall construction, self-supporting, with frontal actuator, with water condensation insulation. Dual-Flush 6/3-l (4/2-l-flush). Flush valve with silicon seal. Fill valve with anti-siphon system.	Accessories excl.	Actuator plates dual flush, order no. 89566.1, 89566.2 (stainless steel) Electronic actuator plate dual flush, order no. 89566.3, 89566.4 Support bar for handle and holding systems, order no. 89266.7, 89266.8
Other specifications	Galvanized leg supports, rotatable, height-adjustable 0-200 mm. Supporting frame made of steel profiles. Capable to resist 400 kg	Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. Height from finished floor to top of WC pre-set to 400 mm, adjustable between 390-450 mm. System installation is also possible between modular walls (plasterboard).
Water inlet	top or rear R 1/2", brass	Colours	Surface powder coated blue
Outlet	DN 90/110		
Flow pressure range	0.5-10 bar		
Water temperature	max. 25°C		
Tank	Thickness 110 mm, material PP		
Installation depth	140-195 mm		

#### TECHNICAL DRAWINGS / S 1 : 20

