



Product certificate K23075/04

Issued 2018-07-01

Replaces K23075/03

Page 1 of 3

Flushing Cisterns

STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

TECE GmbH

as specified in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate may, on delivery, be relied upon to comply with Kiwa evaluation guideline BRL-K620/05 "Flushing Cisterns".

Luc Leroy
Kiwa

Publication of this certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

CERTIFICATE

288171015

Kiwa Nederland B.V.

Sir Winston Churchillaan 273
P.O. BOX 70
2280 AB RIJSWIJK
The Netherlands
Tel. +31 88 998 44 00
Fax +31 88 998 44 20
info@kiwa.nl
www.kiwa.nl

Company

TECE GmbH
Hollefeldstraße 57
48282 EMSDETTEN
Germany
Tel. (+49) 02572 / 9280
info@dece.de
www.dece.de

Certification process
consists of initial and
regular assessment of:

- quality system
- product



Flushing Cisterns

Technical specification

The products mentioned below belong to this certificate

Concealed flushing cisterns using a flush volume of 6 ± 0.2 litres

Flushing cistern S3 (SP190 000 00), with side connection, provided with flush pipe and equipped with:

- float valve *Abu Plast GmbH, type Univ 510 (with brass threaded connection)*
- flushing device *TECE, Ablaufventil standard - type SP229 006 00* with interrupting flush
- flexible hose *Parigi Group International S.p.A, type DN8*
- angled connecting cock *VA Albertoni Rubinetto, type SL012.270*

In various designs with the following product numbers:

- No. 9.240.2xx – Manual dual flush panel (xx=color variations)
- No. 9.240.3xx – Infra-red flush panel (xx = 12V and color variations)

Flushing cistern S4 (SP190 002 00), with side connection, provided with flush pipe (elbow) and equipped with:

- float valve *Abu Plast GmbH, type Univ 510 (with brass threaded connection)*
- flushing device *TECE, Ablaufventil standard - type SP229 006 01* with interrupting flush
- flexible hose *Parigi Group International S.p.A, type DN8*
- angled connecting cock *VA Albertoni Rubinetto, type SL012.270*

In various designs with the following product numbers:

- No. 9.240.2xx – Manual dual flush panel (xx=color variations)

Flushing cistern S5 (SP190 004 00), with side connection, provided with flush pipe (elbow) and equipped with:

- float valve *Abu Plast GmbH, type Univ 510 (with brass threaded connection)*
- flushing device *TECE, Ablaufventil schmall - type SP229 005 00* with interrupting flush
- flexible hose *Parigi Group International S.p.A, type DN8*
- angled connecting cock *VA Albertoni Rubinetto, type SL012.270*

In various designs with the following product numbers:

- No. 9.240.xxx – Manual dual flush panel (xxx=color variations)

Flushing Cisterns

Application and use

The flushing cisterns are intended to operate in combination with WC-pans as hygienical flushing devices to be connected to drinking water installations with a watertemperature of maximum 30°C. Flushing cisterns with an affective flushing volume of $6 \pm 0,2$ Litres are designed for connection to WC-pans of the type 6A (see also Kiwa BRL-K619).

Marking

The Kiwa®-mark products are marked with the wordmark "KIWA"

Place of the mark:

- on the cisterns on the left side, right side or front or on the inside above water level;
- on the body of the float operated valve (filling valve).

Compulsory specifications:

name or mark of the manufacturer

- on the float valves on the body;
- on the cisterns on the left side, right side or front or on the inside above water level.

Method of marking:

- indelible;
- visible after assembly (for concealed flushing cisterns after demounting of the control panel).

RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- TECE GmbH

and, if necessary,

- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.