

Van Marcke Logistics nv

Weggevoerdenlaan 5 - 8500 Kortrijk Tel. +32 (0)56 23 75 11 BTW BE 0443.343.943 - RPR Kortrijk - BIC GEBABEBB - IBAN BE15 2850 2088 4230

DECLARATION OF PERFORMANCE

No. VM00002-ENG-20130409

1.	Unique identification code of the product-type	For product number, please see attached file
2.	Product type	WC Coupled Pans
3.	Intended use(s)	Personal hygiene
4.	Manufacturer	Van Marcke Logistics, Weggevoerdenlaan 5, 8500 Kortrijk
5.	Authorised representative	Not relevant
6.	System/s of AVCP	System 4
7.	a) Harmonised standard	EN 997:2012
	Notified body(ies)	
	b) European Assessment Document	
	European Technical Assessment	
	Technical Assessment Body	
	Notified body(ies)	

8. Declared performance(s)

Close-coupled Suite, an Close-coupled Suite, and one piece and independent WC pan with integral tra

Clause No.	Essential Characteristics ZA.1.1	Performance	Harmonized Technical Specification
5.2.1 - 5.5.4	Capacity of flushing water	Pass	
5.1	Back flow prevention (Foul Air)	Pass	
5.2.2 - 5.2.3 - 5.2.4	Cleanability	Pass	
5.4	Load Resistance (Wall Hung)	NA	En 997:2012
5.5.5	Water/leak tightness	Pass	
5.5.6 - 5.5.7	Valve reliability	Pass	
5.6	Durability	Pass	

WC Suite of Class 2 WC Suite of Class 2

Clause No.	Essential Characteristics ZA.1.2	Performance	Harmonized Technical Specification
6.3 - 6.4 - 6.5 - 6.8	Capacity of flushing water	NA	
6.2 - 6.13	Back flow prevention(foul air and water)	NA	
6.9 - 6.10 - 6.11 - 6.12	Cleanability	NA	
6.14	Load resistance (Wall Hung)	NA	EN 997:2012
6.7 - 6.8	Water/leak tightness	NA	
6.7	Valve reliability	NA	
6.16	Durability	NA	

9. Appropriate Technical Documentation and/or Specific Technical Documentation:

Class 1 Class 2

EN997 Clause		Pass or Fail		EN997 Clause	Pass or Fail
5.1	Depth of Water seal	Pass	6.1	Inlet valve	NA
5.2.1	WC Pan Type	6	6.2	Back flow prevention	NA
5.2.2	Wash of bowl	Pass	6.3	Marking of Cistern	NA
5.2.3	Flushing Toilet paper	Pass	6.4	Warning pipe and overflow provision	NA
5.2.4	Flushing of 50 Plastic balls	N/A	6.5.1	Full Flush vol	NA
5.2.5	Oversplashing	Pass	6.5.2	Reduced flush Vol.	NA
5.2.6	After flush Volume	Pass	6.6	Flush rate	NA
5.3	Water absorption	Pass	6.7	Physical Endurance-leak test	NA
5.4	Static load (Wall Hung)	NA	6.8	Chemical endurance	NA
5.5.2	Inlet Valve	Pass - Appendix B	6.9	Solids discharge and after flush vol	NA
5.5.3	Supply Piping	NA	6.10	Paper discharge reduced flush vol.	NA
5.5.4	Flush Volume of Suits	Pass	6.11	Liquid Contaminant dye retention	NA
5.5.5	Leak tightness Cistern-Bowl	Pass	6.12	Wash of bowl	NA
5.5.6	Valve Leak tightness	Pass - Appendix B	6.13	Depth of water seal	NA
5.5.7	Valve reliability	Pass - Appendix B	6.14	Static load (Wall Hung)	NA
5.5.8	Overflow	Pass	6.15	Water absorption	NA
5.5.9	Safety Margin - Dimension "c"	Pass	6.16	Durability	NA
5.5.10	Safety Margin - Dimension"a"	Pass			
5.6	Durability	Pass			

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NameFrancisco Hernandez	
At (place)Kortrijk	
On (date of issue)09/04/2013	
Signature	

