


**Geberit PE kogelstuk 88,5° dubbel, aansluitingen onder 90°**



**Gebruik**

- Voor de gebouwfvoer

**Kenmerken**

- UV-bestendig

**Technische gegevens**

Materiaal

PE-HD

**Artikel**

Art. nr.	DN	d, ø [mm]	d1, ø [mm]	D [cm]	H [cm]	X1 [cm]	X2 [cm]	X3 [cm]	K1 [cm]	K2 [cm]	K3 [cm]
364.320.16.1	60 / 60	63	63	10	16	8	10	8	1,5	4,5	1,5
365.325.16.1	70 / 70	75	75	12	16	8	10	8	1,5	3,5	1,5
366.330.16.1	90 / 90	90	90	14	18	9	11	9	2	4	2
367.315.16.1	100 / 56	110	56	17	20	10	12	10	1,5	1,5	1,5
367.320.16.1	100 / 60	110	63	17	20	10	12	10	1,5	1,5	1,5
367.325.16.1	100 / 70	110	75	17	20	10	12	10	1,5	1,5	1,5
367.330.16.1	100 / 90	110	90	17	20	10	12	10	1,5	1,5	1,5
367.335.16.1	100 / 100	110	110	17	20	10	12	10	1,5	4	1,5
368.335.16.1	125 / 100	125	110	18	20	10	12,5	10	1,5	4	1,5
369.335.16.1	150 / 100	160	110	23	25	12,5	16	12,5	2	1,5	2